



**HELLENIC GAS  
TRANSMISSION  
SYSTEM OPERATOR**

357-359, MESSOGION AVE.,  
15231 ATHENS, GREECE  
Tel.: 210 6501258  
Fax : 210 6501551

**TECHNICAL JOB  
SPECIFICATION**

**639/1**

**REVISION 0**

**DATE 05/04/2011**

# **HIGH PRESSURE (HP) TRANSMISSION SYSTEMS**

## **SAFETY RELIEF VALVES**



**HELLENIC GAS TRANSMISSION SYSTEM OPERATOR**

**Job Spec. No** 639/1  
**Revision** 0  
**Date** 05-04-2011  
**Page** 2/7

**QUALITY ASSURANCE PAGE**

**CHANGES LOG**

**REVISIONS LOG**

0	05-04-2011	FIRST ISSUE	PQ DPT.	V.G.
<b>Rev. No</b>	<b>Rev. Date</b>	<b>REASON FOR CHANGE</b>	<b>Made By</b>	<b>Approved By</b>

**Job Spec. No** 639/1  
**Revision** 0  
**Date** 05-04-2011  
**Page** 3/7

**CONTENTS**

- 1.0 SCOPE**
- 2.0 GENERAL REQUIREMENTS**

**Job Spec. No** 639/1  
**Revision** 0  
**Date** 05-04-2011  
**Page** 4/7

**REFERENCED DOCUMENTS**

Job Specification 830/1  
[External Painting]

Job Specification 970/2  
[Shop Inspection of Equipment and Materials for NGT Project]

EU Directive 97/23/EC PED  
[Pressure Equipment Directive]

ELOT EN 1092-1  
[Flanges and their joints - Circular flanges for pipes, valves, fittings and accessories, PN designated - Part 1: Steel flanges]

ELOT EN ISO 4126-1 (harmonized to PED)  
[Safety Devices for Protection Against Excessive Pressure - Part 1: Safety Valves]

ELOT EN ISO 4126-4 (harmonized to PED)  
[Safety Devices for Protection Against Excessive Pressure - Part 4: Pilot Operated Safety Valves]

ELOT EN ISO 8434  
[Metallic tube connections for fluid power and general use]

DIN 2353  
[Compression Fittings and Couplings]

1.0 **SCOPE**

1.1 **ITEM**

Safety Relief Valves with a maximum operating pressure < 100 bar.

1.2 **SERVICE**

Non corrosive Gas.

1.3 **APPLICATION**

Relieving of overpressure in piping systems due to leakage through closed pressure regulating valves, or ON/OFF valves.

2.0 **GENERAL REQUIREMENTS**

2.1 **LEGISLATION AND STANDARDS**

The requirements deriving from the **EU Directive 97/23/EC PED** for pressure equipment shall be considered.

Safety Relief Valves shall conform to the requirements specified in **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**.

2.2 **UNITS**

Metric.

2.3 **TYPE**

Spring loaded or pilot operated.

2.4 **CONSTRUCTION**

2.4.1 **GENERAL**

Safety relief valves may be of the conventional or balanced type and shall remain leak proof after discharge.

2.4.2 **PILOT OPERATED**

Non-flowing pilots shall be used to minimize entrance of dirt and formation of hydrates in the pilot.

Modulating pilots shall be used in cases during which variable relief loads are expected.

Pilot operated safety relief valves should be used if the sum of the superimposed and built-up back pressures exceeds 50% of the set point pressure, or when the operating pressure is quite close to the set pressure (usually greater than 90% of the set pressure).

Pilot operated safety relief valves shall be of the fail open type.

2.4.3 **CONVENTIONAL TYPES**

Conventional type safety relief valves may only be used if the sum of the superimposed and build-up back pressures does not exceed 10% of the set point pressure. Additionally the bonnet of the valve shall be vented to the discharge side of the valve.

2.4.4 **SEALS**

Soft type.

- 2.4.5 **BLOW DOWN**  
Shall not exceed 5% of the set pressure.
- 2.4.6 **INLET/OUTLET CONNECTIONS**  
Raised face flanges according to **ELOT EN 1092-1**.
- 2.4.7 **AUXILIARY PIPING AND CONNECTIONS**  
Auxiliary piping and fittings shall be made of stainless steel.  
Fittings shall conform to **DIN 2353** and **ELOT EN ISO 8434**.  
If the specified fittings are not supplied adaptor fittings shall be delivered.
- 2.4.8 **CAPACITY CONVERSIONS**  
Shall be determined in accordance with the **ELOT EN 4126-1**.
- 2.5 **MATERIALS**  
All materials that are going to be used shall conform to with **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**.
- 2.6 **SURFACE TREATMENT**  
Refer to **Job Specification 830/1**.
- 2.7 **TESTING**  
A capacity certification test for each valve shall be done in accordance with **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**.  
The primary pressure parts of each valve shall be tested at a pressure of at least 1.5 times the maximum allowable operating one.  
Each valve assembly shall be tested to its set pressure.  
A seat tightness test for each valve shall be done according to **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**.  
The medium for all tests shall be in accordance with **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**.
- 2.8 **TYPE TEST**  
The complete safety relief valve shall be type test approved by an Independent Accredited Inspection Body.
- 2.9 **MARKING**  
Each safety relief valve shall be fitted with a stainless steel marker plate, indicating all relevant technical data required by **EU Directive 97/23/EC PED** and **ELOT EN ISO 4126-1** and **ELOT EN ISO 4126-4**, together with the contract and item tag numbers.
- 2.10 **INSPECTION AND CERTIFICATION**  
Inspection will be performed by an Accredited Inspection Body appointed by Owner.  
Inspection requirements are defined in the following documents.  
a. Material requisition.  
b. **Job Specification No 970/2**.  
c. Relevant project specifications.

**Job Spec. No** 639/1  
**Revision** 0  
**Date** 05-04-2011  
**Page** 7/7

d. Inspection clauses of applicable Standards.

Inspection procedures to be followed are detailed in Owner document "Inspections and Test Instructions for the Project".

## **2.11 COMPLIANCE WITH THE EU DIRECTIVES**

All parts that comply with the "New Approach" directives shall be provided with:

- a. A physical CE marking and other information as required by the relevant directives.
- b. A declaration of conformity which lists all the directives with which the product complies.
- c. Any other information specified by the directive, e.g. user instructions.